



Series: **Vapor Proof Series**      Fixture Type: **Large LED Surface Mount Vapor Proof**

| Project Name         | Fixture Type         | Catalog #            | Quantity             |
|----------------------|----------------------|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |



VPW

### Design Features / Specifications

**HOUSING:** Heavy Duty Die Cast Aluminum Housing & Screw On Guard, 3/4" NPS Threaded Mounts.

**LENS:** Clear Glass

**LED Module:**

Luminous Flux: 800lms  
 CRI: 80  
 CCT: 4000K & 5000K  
 Operating Temperature: -40°C to +40°  
 50,000 hrs  
 IP66 Sealed LED Compartment

**WATTAGE:** 10W

**MOUNTING:** Surface Mount

**ACCESSORIES:** (Order Separately, Field Installed)

AAS - Angled Aluminum Shade, Repaint-able Textured Gray Finish. 8 3/4" Dia. by 11 3/4" Dia.  
 WGA - Wire Guard for Angled Shade, Stainless Steel  
 CRB5.5 - Die Cast Round Electrical Box with Five (5) 1/2" Coin Plugs  
 BPCP.5 - Backplate, 1/2" Coin Plugs  
 CRB5.75 - Die Cast Round Electrical Box with Five (5) 3/4" Coin Plugs


**LISTINGS & RATINGS:**

CSA: Listed for Wet Locations  
 Other Wattages & Custom Colors Available Upon Request.

### Dimensional Information



### Photometric Information



| Vapor Proof Series   |   |
|--|---|
| Catalog #  | Description   |
| <b>Complete Units Ordering Information</b><br>Example: VPW-L-1X-10-UNV-50K-C-G-G-G |   |
| <b>VPW</b>   | <b>Fixture Series:</b> VPW = Vapor Proof (Surface mnt) Large Style  |
| <b>L</b>   | <b>Light Source:</b> L = Light Emitting Diode (LED)                 |
| <b>1X</b>  | <b>Number of LED Arrays:</b> 1X = One                               |
| <b>10</b>  | <b>Wattage:</b> 10 = 10W  |
| <b>UNV</b>   | <b>Driver Voltage</b> UNV=Universal Voltage (120v-277v)             |
|  | <b>Color Temperature:</b> 40K = 4000K<br>50K = 5000K                |
| <b>C</b>   | <b>Lens Type</b> C = Clear Glass Globe                              |
| <b>G</b>   | <b>Lens Guard Type</b> G = Die Cast Aluminum Guard                  |
|  | <b>Lens Guard Color</b> G = Gray (Standard)<br>C = Custom (Specify) |
|  | <b>Housing Color</b> G = Gray (Standard)<br>C = Custom (Specify)    |
|  | <b>Options*</b> (Blank) = None<br>SF = Single Fuse                  |

\* Contact Factory for all Other Options

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.