



Series:
NEMA 4X Wet Location Exit Sign (INDWL)

Fixture Type:
Exit Sign

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



NEMA 4X Wet Location Exit Sign (HEZXS)

Catalog #	Description
Complete Units	
Ordering Information Example: INDWL-1-R-W-SDT	
INDWL	Model: INDWL EMA 4X Wet Location Exit Sign
	# of Faces: 1 = Single Face 2 = Double Face
	Letter Color: R = Red G = Green
	Housing Color: W = White B = Black
	Battery: (Blank) = AC-Only EM = Battery Back-up
	Options: SDT = Self-diagnostic ¹ TP = Tamper proof
Notes:	1. EM Units only

Design Features / Specifications

ILLUMINATION

Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL

Dual 120/277 voltage. Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery). Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing. 4.8V long-life, maintenance-free, rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

Universal knockout pattern on back provided with gasket for watertight seal for back mount. Polycarbonate mounting canopy included for top or end mount

HOUSING

Housing is reinforced polycarbonate construction in gray finish. Corrosion-resistant enclosure with one piece, high impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws. EZ snap-out Chevron directional indicators.

WARRANTY / LISTING

Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. IP66 rated for Ingress Protection. NEMA4X and NSF rated up A, B, C, & D. Certified to CEC under Title20 Regulations. UL listed for wet locations (-20°C – 50°C). Five year warranty on all electronics and housing. Battery pro-rated for five years.

Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
INDEWL	2.5	2.5	0.025	0.010

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Dimensional Information

